

RXH/N2

ES

Montaje: Empotrado.

Fuente de luz: Módulo compacto LED COB.
Temperatura de color seleccionable 3000K, 4000K, 6000K.

Sistema óptico: Reflector facetado.

Distribución luminosa: Directa. Óptica 36°.

Equipo eléctrico: Equipo de control electrónico. PF>0,95. Disponible, regulable 1-10V o DALI y/o Kit de emergencia (1-3 h).

Materiales: Cuerpo: Fundición de aluminio en blanco. Reflector: Aluminio anodizado facetado. Aro: Fundición de aluminio. Cubierta: Difusor PC.

Acabado: Aro: Fundición de aluminio en color blanco RAL 9003.



EN

Mounting: Recessed.

Light source: LED compact module COB.
Selectable emperature color 3000K, 4000K, 6000K.

Optical system: Faceted reflector.

Light distribution: Direct. Lens 36°.


Electrical equipment: Electronic control gear. PF>0,95. Available, dimmable 1-10V or DALI, and/or emergency Kit (1-3 h).

Materials: Body: Die-cast aluminum in white. Reflector: Faceted anodized aluminum. Trim: Die-cast aluminum. Cover: PC diffuser.

Surface finish: Trim: Die-cast aluminum in white colour RAL 9003.



RXH/N2-190-40W




FLICKER FREE




<19




160




Ø190 mm



120



330°



80°

ESTANDAR/STANDARD



5 AÑOS
5 YEARS



220-240V
50-60Hz



IP 20



IK 04



CLASE II
CLASS II



50.000h
L80B10



-20°
+40°



CRI 80



36°



3000K
4000K
6000K



1-10V
DALI



1h
3h

DISPONIBLE/AVAILABLE

CONFIGURACION ONLINE ONLINE CONFIGURATION



Código Code	Referencia Reference	Kg Kg	Potencia Power	Lúmenes Lumens	Eficiencia Efficiency	CCT (K) CCT (K)
RXH414K0B	RXH/N2-190-40W 4200lm/830-840-860	0,9	40W	4200	105 lm/W	3000, 4000, 6000

ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMING 1-10V | DALI KIT DE EMERGENCIA/EMERGENCY KIT 1h | 3h REGULADOR DE LUZ + DETECTOR DE PRESENCIA (RLP)/AMBIENT LIGHT + PRESENCE SENSOR (RLP)
DETECTOR DE PRESENCIA (SLP)/PRESENCE DETECTOR (SLP) ARO ADAPTADOR/ADAPTER RING