

TPBL/MICROPRISMA IP65 1200x300 mm

ES




Montaje: Empotrable.
Fuente de luz: Módulos lineales LED SMD.
 Temperatura de color seleccionable, CCT: 3000K, 4000K, 6000K.
Sistema óptico: Difusor microprismático.
Distribución luminosa: Directa.
Equipo eléctrico: Equipo de control electrónico. PF>0,95.
 Disponible, regulable 1-10V o DALI y/o kit emergencia (1-3 h).
Materiales: Cuerpo: Acero de alta resistencia a la torsión. Marco de la luminaria: Aluminio extruido lacado en blanco de diseño profesional.
 Difusor: Microprismático.
Acabado: Color blanco RAL9003.

EN



Mounting: Recessed.
Light source: LED linear modules SMD.
 Selectable temperature color, CCT: 3000K, 4000K, 6000K.
Optical system: Microprismatic diffuser.
Light distribution: Direct.
Electrical equipment: Electronic control gear. PF>0,95.
 Available, dimmable 1-10V or DALI and/or emergency kit (1-3 h).
Materials: Body: High resistance steel. Frame: Professional design of extruded aluminum lacquered in white. Diffuser: Microprismatic.
Surface finish: White color RAL 9003.

TPBL/MICROPRISMA-IP65-40W



SENSOR DE LUZ Y PRESENCIA
LIGHT AND PRESENCE SENSOR



MARCO PARA EMPOTRAR
ACCESSORY FOR RECESS




GARRAS PARA TECHOS CLIP IN
BRACKETS FOR RECESS



ACCESORIO PARA ADOSAR
ACCESSORY FOR SURFACE



IP-65 SALAS BLANCAS
CLEAN ROOM



ESTANDAR/STANDARD

5 AÑOS / 5 YEARS
 220-240V / 50-60Hz
 IP 65
 IK 02
 CLASE II / CLASS II
 50.000h L80B10
 -20° / +40°
 CRI 80
 3000K / 4000K / 6000K

DISPONIBLE/AVAILABLE

1-10V DALI
 EMERGENCY KIT 1h / 3h

CONFIGURACION ONLINE ONLINE CONFIGURATION



Código Code	Referencia Reference	Kg	Potencia Power	Lúmenes Lumens	Eficiencia Efficiency	CCT(K) CCT(K)
TPMDP4KCB	TPBL/MICROPRISMA-IP65-32W 4400lm/830-840-860 PH	1,3	32W	4400	137 lm/W	3000, 4000, 6000
TPMDP5KCB	TPBL/MICROPRISMA-IP65-40W 5250lm/830-840-860 LM	1,3	40W	5250	131 lm/W	3000, 4000, 6000
TPMDP52CB	TPBL/MICROPRISMA-IP65-40W 5250lm/830-840-860 PH/TR	1,3	40W	5250	131 lm/W	3000, 4000, 6000

ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMING 1-10V | DALI KIT DE EMERGENCIA/EMERGENCY KIT 1h | 3h ACCESORIO PARA EMPOTRAR/ACCESSORY FOR RECESS KIT PARA EMPOTRAR/KIT FOR RECESS
 KIT PARA ADOSAR/KIT FOR SURFACE ACCESORIO PARA ADOSAR/ACCESSORY FOR SURFACE SUJECION PARA TECHO DE ESCAYOLA/FRAME FOR PLASTER CEILING
 GARRAS PARA TECHO CLIP-IN, TECHO OCULTO.../BRACKETS FOR CLIP-IN CEILING, HIDDEN CEILING... DETECTOR DE PRESENCIA (SLP)/PRESENCE DETECTOR (SLP)